

Metal Cement 850

06/2009

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Metal Cement 850 Product Type: Retaining Compound

Company: Hernon Manufacturing, Inc. Contact Information: Telephone: 407-322-4000

121 Tech Drive Emergency Telephone: 800-255-3924

Sanford, FL 32771 Web Site: www.hernonmfg.com

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Ingredients</u>	%	ACGIH TLV	OSHA PEL	<u>OTHER</u>	
Hydroxyalkyl Methacrylate	30-60	None	None	1ppmTWA 3ppm STEL	
Aromatic Dimethacrylate Ester	30-60	None	None	None	
Bisphenol A Fumarate Resin	10-15	None	None	None	
Silica, fumed	5-10	6 mg/m³ TWA	10 mg/m³ TWA	3 mg/m³ TWA respirable dust	
Cumene Hydroperoxide	1-3	None	None	1 ppm (6 mg/m³) Skin (WEEL)	
1-Acetyl-2-phenylhydrazine	0.1-1	None	None	None	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state: Paste HEALTH: 2
Color: Silver FLAMMABILITY: 1

Odor: Mild PHYSICAL HAZARD: 1

Personal Protection: See Section 8

WARNING: CAUSES EYE, AND SKIN IRRITATION.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

MAY BE HARMFUL IF SWALLOWED.

Primary Routes of Entry: Skin, Inhalation, Eyes, Ingestion

Signs and Symptoms of Exposure:

Inhalation: May cause respiratory tract irritation.

Skin contact: Irritating to skin. May cause allergic skin reaction.

Eye contact: Contact with eyes will cause irritation.

Ingestion: May be harmful if swallowed.

Existing Conditions Aggravated by Exposure: Eye, skin, and respiratory disorders.



Metal Cement 850

06/2009

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin Contact: Wash with soap and water. Remove contaminated clothing and shoes. Wash

clothing before reuse. Get medical attention if symptoms occur.

Eye Contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash Point (TCC): > 200°F

Recommended Extinguishing Agents: Carbon dioxide, foam, dry chemical

Special Firefighting Procedures: None

Hazardous Combustion Products: Oxides of carbon. Oxides of nitrogen. Irritating organic vapors.

Unusual Fire or Explosion Hazards: None

Flammable/Explosive Limits – lower %: Not available
Flammable/Explosive Limits – upper %: Not available

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear proper protective equipment

Measures for Environmental Protection: Do not allow entry into drains or surface waters

Clean-up Measures: Soak up with an inert absorbent. Store in partly filled, closed container until

disposal.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation.

Storage: Store between 46° and 82°F unless otherwise labeled to preserve shelf life.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Eye/Face Protection: Safety glasses or goggles with side shields

Skin Protection: Use rubber or plastic gloves, and protective clothing as necessary

Respiratory Protection:Use NIOSH approved respirator if there is a potential to exceed exposure

limits

Engineering Controls: Forced ventilation may be required if concentrations exceed exposure limits



9.

Metal Cement 850

06/2009

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Paste
Color: Silver
Odor: Mild

Vapor Pressure: Less than 5 mm at 80°F

Vapor Density: Not available

Solubility in Water:

Specific Gravity:

1.12

Boiling Point:

Volatile Organic Compound Content

38.1%

Evaporation Rate (Ether = 1) Not available

pH: Does not apply

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Hazardous Decomposition Products: Oxides of carbon. Oxides of nitrogen. Irritating organic vapors.

Incompatibility: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

	Literatu	Literature Referenced Target Organ					Carcinogen Status			
Ingredients:	and Ot	and Other Health Effects					IARC	OSHA		
Hydroxyalkyl Methacrylate	ALG	IRR				NO	NO	NO		
Aromatic Dimethacrylate Ester	ALG	IRR				NO	NO	NO		
Bisphenol A Fumarate Resin	ALG	IRR				NO	NO	NO		
Silica, fumed	NTO					NO	NO	NO		
Cumene Hydroperoxide	ALG	CNS	COR	IRR	MUT	NO	NO	NO		
1-Acetyl-2-phenylhydrazine	ALG	BLO	MUT	KID	SOM	NO	NO	NO		

Abbreviations:

IRR IrritantMUT MutagenNTO No Target OrgansCOR CorrosiveKID KidneyCNS Central Nervous System

ALG Allergent BLO Blood SOM Evidence of Some Carsinogenicity

12. ECOLOGICAL INFORMATION

Water Hazard: Do not allow entry into drains or surface waters



Metal Cement 850

06/2009

13. DISPOSAL CONSIDERATIONS

Recommended methods of disposal: Dispose of according to Federal, State and Local regulations.

EPA Hazardous Waste Number: Not an RCRA hazardous waste

14. TRANSPORTATION INFORMATION

U.S. Dept. of Transportation Ground (49 CFR):

Proper Shipping Name Unrestricted

Hazard Class or Division:

Identification Number

None

Packing group:

None

International Air Transportation (ICAO/IATA):

Proper Shipping Name: Unrestricted

Hazard Class or Division:

Identification Number

None

Packing group:

None

WaterTransportation (IMO/IMDG):

Proper Shipping Name: Unrestricted

Hazard Class or Division:NoneIdentification NumberNonePacking group:NoneMarine pollutant:None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances

Control Act Inventory

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting

requirements of section 313 of the Emergency Planning and Community

Right-To-Know Act of 1986 (40 CFR 372): Cumene Hydroperoxide

16. OTHER INFORMATION

Prepared By: Jerry Litteral

Title: Director - Quality & Development

DISCLAIMER: Some of the information presented is from sources other than direct test data on the product itself. The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.