

RyFlor™ Joint Sealant

Adaptable, Flexible, & Easy to Use

RyFlor™ RF40 joint sealant is our versatile, malleable, and highly compressible gasket. It's commonly used to seal flanges, joints, and tank doors. Under pressure, it fills surface irregularities, deformations, and deflection, providing a tight, leak-free seal.

With RyFlor™'s excellent chemical resistance, our joint sealant can withstand harsh, demanding applications. It has a general temperature range of -268°C to 316°C (-450°F to 600°F). The material can also endure a wider range of pressure and temperature than other soft gaskets. It is FDA-compliant, making it safe for food and beverage, sanitary, and brewing applications.

Our RyFlor™ RF40 joint sealant is distributed on spools in various cross-sections and lengths. It has a peelable adhesive tape backing that allows for easy installation and removal.

Nominal Width	Thickness	Feet/Spool	Flange Size
1/8"	0.059"	100, 1000	1/2" to 3/4"
3/16"	0.079"	100, 1000	1" to 1-1/2"
1/4"	0.098"	50, 100, 500	2" to 3-1/2"
3/8"	0.12"	25, 50, 250	4" to 6"
1/2"	0.20"	15, 30, 150	8" to 16"
5/8"	0.24"	15, 30, 150	17" to 20"
3/4"	0.28"	15, 30, 50, 100	24" to 36"
1"	0.39"	15, 30, 75	36" to 60"
2"	0.39"	39	60" and up

